

2100™

LIGHTBARS



THE 2100 FEATURES AN INCREDIBLY BRIGHT SIGNAL IN A SLEEK, COMPACT PACKAGE

Powerful LED emergency lighting in a low profile lightbar—just 2.1" tall.

Design Features

Optix, LED X, and LC-LED modules generate bright, powerful signals with rich, true colors.

Sleek design results in less drag and better fuel efficiency.

Solid-state LEDs draw only 0.5 amp per module, minimizing energy consumption and heat generation.

Clear lenses and the absence of color in the unlit lightbar make it inconspicuous until illuminated.

Easy to install LIT3 mounting platform.

Powered through a standard 12-volt input. All voltage management handled through the integrated light engine and optics of the Optix, LED X and LC-LED modules.

5-year warranty on LED modules.

Options

Build-Your-Own Base Models

LED or Halogen ArrowStik®

Lighted LIT3 Mounting Kit (LED and/or 55W Halogen)

Specifications

36", 47", 58", 69", 80" and 91" Lengths

12.25"W x 2.1"H









12 Volt

Meets all applicable SAE, NFPA and California Title 13 specifications when properly configured.



2100 with Optix

STANDARD 47" CONFIGURATIONS



2100 LIGHTBAR KEY			
OPX OPTIX 6-UP LED CORNER MODULE	LC LC-LED MODULE	A 35W ALLEY LIGHT	BUILT-IN HALOGEN ARROWSTIK
OPX6 OPTIX 6-UP LED MODULE	35 35W MR-11 STATIONARY	A8 MR-8 ALLEY LIGHT	BUILT-IN LED X ARROWSTIK
LED LED X SINGLE MODULE	27 27W STATIONARY HALOGEN	A11 MR-11 ALLEY LIGHT	BUILT-IN LC-LED ARROWSTIK
OPX 33 OPTIX (2) 3-UP LED MODULE	35 35W HALOGEN ANGLED TAKEDOWN	D.O.T. LIGHTS	BUILT-IN OPTIX ARROWSTIK

