

FMVSS Certified Stop/Turn/Tail LED Lights



Design Features

- 4" Round and 6" Oval Signaling LED Light Module
- Nineteen LEDs in Each Light
- High Intensity Amber or Red LED Standard
- 5-Year Warranty

Options

- Amber Lens with Amber LEDs
- Red Lens with Red LEDs

Specifications

- Round: 4" Diameter x 2.3" Height (178 mm x 57 mm)
Oval: 6" Diameter x 2.3" Height x 1.9" Depth (164mm x 58mm x 48mm)
- 12-24 VDC
- Weight: 0.7 lb
- Polarity: Negative Ground Only and Polarity Protected
- 0.05 Amp Peak Current at 12VDC
- DOT FMVSS108 and Related SAE Standards Compliant:
DOT SAE S2 for Stop Light
DOT SAE1 for Turn Light
DOT SAE T2 for Tail Light
DOT SAE R for Back-up Light

Round Model Numbers

RNDSTTRH: 4" Round, Red

RNDSTTAH: 4" Round, Amber

Oval Model Numbers

OVLSTTRH: 6" Oval, Red

OVLSTTAH: 6" Oval, Amber

Featuring Self-Contained Flasher Units



Round LED Design Features

- 39 LEDs, Available in Amber or Red
- **4 Flash Patterns:** Single, Double, Quad, Steady Burn
- 70 Flashes per Minute

Specifications

- 1.4" Depth (31.75 mm)
- Weight: 0.5 lbs.
- 12/24 Volt DC
- 0.3 Average Amp Draw
- SAE J595, Class II

Standard Models

4" Round, Synchronous or Alternating Flash (101.6 mm)

Model	LED Color	Lens Color
RNDALS1H	Amber	Amber
RNDRLS1H	Red	Red

Oval LED Design Features

- 22 LEDs, Available in Amber or Red
- **4 Flash Patterns:** Single, Double, Quad, Steady Burn
- 70 Flashes per Minute

Specifications

- 1.55" Depth
- Weight: 0.4 lbs.
- 0.2 Average Amp Draw
- SAE J595, Class II

Standard Models

6" Oval, Synchronous or Alternating Flash (152.4 mm)

Model	LED Color	Lens Color
OVLALS1H	Amber	Amber
OVLRLS1H	Red	Red